

**Thank you for your purchase of the  
ULTRA & ULTRA-UC REPLACEMENT CARTRIDGE SET**

**IMPORTANT!** – The “This End Up” marking on the AntiRad-Plus<sup>TM</sup> cartridge only applies to undercounter systems, for countertop systems this end must be facing down.

**CAUTION!** - For undercounter systems, please ensure you have turned off the water supply at the cold water line & opened the dedicated faucet (to release pressure) before opening the systems.

**CARTRIDGE CHANGE INSTRUCTIONS**

1.  Remove old cartridges. Clean and rinse the system/housings. Recommended: Lubricate O-rings with Food-Grade Silicone Lubricant only. (Available in the “Parts” Section of our website).
2.  Unwrap / remove shrink wrap from the new cartridges
3.  Place **SuperBlock<sup>TM</sup>** Cartridge into Input Chamber #1 & **FluorSorb-MAX<sup>TM</sup>** into Middle Chamber #2
4.  Close **Chamber #3 Empty for now** and flush first two cartridges only for 5 minutes.
5.  Place **AntiRad-Plus<sup>TM</sup>** Cartridge into Output Chamber #3. Flush system 10 more min.
6.  If you have our **Gallon-Meter** Installed: Set it to **500** Gallons on the **Black Arrow**.

*\*Check for any leaks. Water May be cloudy for 1-2 weeks as the cartridges adapt, this is a normal effect of minerals inside (to speed this up, run the system more often throughout the day in short 15-20 second bursts. This is better than leaving it on long, which would waste cartridge life). **Do not lubricate O-Rings on cartridges, only ones inside the housings.** **\*\*If you are storing the set for later, please ensure there are no punctures or holes in the shrink-wrapping, if so, place in ziplock bags to isolate from air.***

