

**Thank you for your purchase of the
ULTRA & ULTRA-UC REPLACEMENT CARTRIDGE SET**

IMPORTANT! – The “This End Up” marking on the AntiRad-PlusTM cartridge only applies to undercounter systems, for countertop systems this end must be facing down.

CAUTION! - For undercounter systems, please ensure you have turned off the water supply at the cold water line & opened the dedicated faucet (to release pressure) before servicing system. If you have our Leak-Stopper Device Installed, ensure to protect it from getting wet during this process.

CARTRIDGE CHANGE INSTRUCTIONS

1. Remove old cartridges. Clean and rinse the system/housings. Recommended: Lubricate O-rings inside housings (**not cartridges**) w/ Food-Grade Silicone only. (Available on our website).
2. Unwrap / remove shrink wrap from the new cartridges
3. Place **SuperBlockTM** Cartridge into Input **Chamber #1** & **FluorSorb-MAXTM** into Middle **Chamber #2**
4. Close **Chamber #3 Empty for now** and flush first two cartridges only for 5 minutes.
5. Place **AntiRad-PlusTM** Cartridge into Output **Chamber #3**. Flush system 10 more min.
6. If you have our **Gallon-Meter** Installed: Set it to **500 Gallons**.

Check for any leaks. Water May be cloudy for 1-2 weeks as the cartridges adapt, this is a normal effect of minerals inside (to speed this up, run the system more often throughout the day in short 15-20 second bursts. This is better than leaving it on long, which would waste cartridge life). Do not lubricate O-Rings on cartridges, only ones inside the housings. **If you are storing the set for later, please ensure there are no punctures or holes in the shrink-wrapping, if so, place in ziplock bags to isolate from air.***

